



Diesel Guard™ AntiGel Deicer

Diesel Guard Antigel Deicer (DGAW) offers superior cold weather operability through the proprietary formulation of ingredients, reducing the need to utilize kerosene blending.

- **Detergents** – clean external tip deposits and Internal Diesel Injector Deposits (IDID) extending engine life
- **Corrosion Inhibitor** – reduces down time and lower maintenance costs by helping prevent fuel system damage and tank corrosion
- **VT101™ Lubricity Enhancer** – prevent premature wear of fuel injectors and pumps
- **VT330A™** - alter the size of wax crystals keeping the crystals more evenly dispersed in the fuel, improving cold flow properties and cold weather performance
- **“SMART” Deicer** – reduces the freeze point to as low as -50°F reducing the formation of ice crystals, preventing gelling, icing and filter plugging
- **Antioxidants** – stabilize the fuel to reduce sludge formation
- **Cetane Booster** – providing easier starts, less smoke and reduced emissions
- **Wax Anti-Settling Agent (WASA)** – Helps keep wax crystals suspended and prevents settling that can plug fuel lines and filters

Diesel Guard Antigel Deicer IS GREAT FOR USE IN

Agricultural & Farming Equipment • Truck Fleets • Construction
Backup Power • Heavy-Duty Diesel Applications

APPLICATIONS

This diesel additive should be used to winterize and improve the quality of high sulfur, low sulfur, ultra-low sulfur and biodiesel blends up to 5% diesel fuels. Typical applications include fleets, farms, construction, power generation, and all other heavy-duty diesel applications

BLENDING RECOMMENDATIONS

Diesel Guard Antigel Deicer should be added directly into the equipment fuel tank prior to adding fuel. Tanks should have a 20% heel of fuel and be free of excess water and/or sludge.

TREATMENT RATIO	
Treat Rate	Cold Temp Operability
1:250	Normal
1:125	Severe



SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

TYPICAL SPECIFICATIONS	
Color (ASTM D1544)	2
Specific Gravity @ 68° F (ASTM D891)	0.8778
Density, lbs./gal. (Calculated)	7.31
Flash Point °F, TCC (ASTM D3278)	126
Additive Pour Point °F (ASTM D97)	-50°F
Viscosity @ 77°F cP (Brookfield)	2.56
NOTE: The sulfur content of this fuel additive does not exceed 15 ppm.	

AVAILABLE PACKAGING

- 8 oz
- 32 oz