



Diesel Guard™ AntiGel Deicer - Concentrate

Diesel Guard Antigel Deicer (AGPW) is a proprietary blend offering superior cold weather operability through cold flow improvers and heavy wax modifiers. These lower the cold filter plug point and break down and prevent wax and ice crystals from clogging filters.

Diesel Guard Antigel Deicer is non-alcohol and absorbs less water than other deicers, resulting in less ice buildup and corrosion in your fuel system and tanks.

- **VT330A™** - alter the size of wax crystals keeping the crystals more evenly dispersed in the fuel, improving cold flow properties and cold weather performance
- **"SMART" Deicer** – reduces the freeze point to as low as – 50°F reducing the formation of ice crystals, preventing gelling, icing and filter plugging
- **Wax Anti-Settling Agent (WASA)** – Helps keep wax crystals suspended and prevents settling that can plug fuel lines and filters



Diesel Guard Antigel Deicer IS GREAT FOR USE IN
 Agricultural & Farming Equipment • Truck Fleets • Construction
 Backup Power • Heavy-Duty Diesel Applications

APPLICATIONS

This diesel additive should be used to winterize and improve the quality of high sulfur, low sulfur, ultra-low sulfur and biodiesel blends of diesel fuels. Typical applications include fleets, farms, construction, power generation, and all other heavy-duty diesel applications

BLENDING RECOMMENDATIONS

Diesel Guard Antigel Deicer should be added to the fuel transport or storage tank prior to adding fuel. Storage tanks should have a 20% heel of fuel and be free of excess water and/or sludge.

TREATMENT RATIO	
Treat Rate	Cold Temp Operability
1:3000	Normal
1:1500	Normal to Severe
1:750	Severe
1:500	Maximum Dosage



SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

TYPICAL SPECIFICATIONS	
Color (ASTM D1544)	2
Specific Gravity @ 68° F (ASTM D891)	0.8946
Density, lbs./gal. (Calculated)	7.45
Flash Point °F, TCC (ASTM D3278)	122
Additive Pour Point °F (ASTM D97)	-25°F
Viscosity @ 77°F cP (Brookfield)	6.18
NOTE: The sulfur content of this fuel additive does not exceed 15 ppm.	

AVAILABLE PACKAGING

- 300 gal totes
- 55 gal
- 2.5 gal