



## **Diesel Guard™ Supreme Plus - Summer**

Diesel Guard Supreme Plus Summer (DGSP) is a proprietary formulation to keep your fuel system performing at its peak. The unique formulation works with all diesel fuel and biodiesel blends.

- **Detergents** – clean external tip deposits and Internal Diesel Injector Deposits (IDID) extending engine life
- **Corrosion Inhibitor** – reduces down time and lower maintenance costs by helping prevent fuel system damage and tank corrosion
- **VT101™ Lubricity Enhancer** – prevent premature wear of fuel injectors and pumps
- **Cetane Booster** – providing easier starts, less smoke and an increase of up to five numbers
- **Antioxidants** – stabilize the fuel to reduce sludge formation

### **Diesel Guard Supreme Plus Summer IS GREAT FOR USE IN**

Agricultural & Farming Equipment • Truck Fleets • Construction  
Backup Power • Heavy-Duty Diesel Applications

### **APPLICATIONS**

This diesel additive should be used to improve the quality of high sulfur, low sulfur, ultra-low sulfur and biodiesel blended diesel fuels. Typical applications include fleets, farms, construction, power generation, and all other heavy-duty diesel applications

### **BLENDING RECOMMENDATIONS**

*Diesel Guard Supreme Plus Summer should be added to the fuel transport or storage tank prior to adding fuel. Storage tanks should have a 20% heel of fuel and be free of excess water and/or sludge.*

<b>TREATMENT RATIO</b>		
<b>Treat Rate</b>	<b>Detergency</b>	<b>Cetane No. Increase</b>
1:3000	Keep Clean/Clean Up	Up to 2
1:2000	Clean Up	Up to 3
1:1500	Rapid Clean Up	Up to 4
1:1000	Rapid Clean Up	Up to 5



### **SAFETY PRECAUTIONS**

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

### **WARRANTY**

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

### **TYPICAL SPECIFICATIONS**

Color (ASTM D1544)	7
Specific Gravity @ 68° F (ASTM D891)	0.9426
Density, lbs./gal. (Calculated)	7.87
Flash Point °F, TCC (ASTM D3278)	152
Additive Pour Point °F (ASTM D97)	<-50°F
Viscosity @ 77°F cP (Brookfield)	7.74
<b>NOTE:</b> The sulfur content of this fuel additive does not exceed 15 ppm.	

### **AVAILABLE PACKAGING**

- 300 gal totes
- 55 gal
- 2.5 gal