



Diesel Guard™ Supreme - Summer

Diesel Guard Supreme Summer (DGSCRD) is a unique formulation to keep your fuel system performing at its peak. Diesel Guard Supreme formulates a high-performance diesel fuel that can prevent injector sticking and fouling in all types of diesel fuel systems including deposit prone High-Pressure Common Rail (HPCR) injectors. Diesel Guard Supreme meets/exceeds DW-10 and XUD-9 performance standards at primary treat rates.

- **Detergents** – clean external tip deposits and Internal Diesel Injector Deposits (IDID) extending engine life
- **Corrosion Inhibitor** – reduces down time and lower maintenance costs by helping prevent fuel system damage and tank corrosion
- **VT101™ Lubricity Enhancer** – prevent premature wear of fuel injectors and pumps even when not in use
- **Antioxidants** – stabilize the fuel to reduce sludge formation
- **Cetane Booster** – providing easier starts, less smoke and reduced emissions

Diesel Guard Supreme Summer IS GREAT FOR USE IN

Agricultural & Farming Equipment • Truck Fleets • Construction
Backup Power • Heavy-Duty Diesel Applications

APPLICATIONS

This diesel additive should be used to improve the quality of high sulfur, low sulfur, ultra-low sulfur and biodiesel blended diesel fuels. Typical applications include fleets, farms, construction, power generation, and all other heavy-duty diesel applications

BLENDING RECOMMENDATIONS

Diesel Guard Supreme Summer should be added to the fuel transport or storage tank prior to adding fuel. Storage tanks should have a 20% heel of fuel and be free of excess water and/or sludge.

TREATMENT RATIO		
Treat Rate	Detergency	Cetane No. Increase
1:3000	Keep Clean/Clean Up	Up to 2
1:2000	Clean Up	Up to 3
1:1500	Rapid Clean Up	Up to 4
1:1000	Rapid Clean Up	Up to 5



SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

TYPICAL SPECIFICATIONS

Color (ASTM D1544)	7
Specific Gravity @ 68° F (ASTM D891)	0.8946
Density, lbs./gal. (Calculated)	7.47
Flash Point °F, TCC (ASTM D3278)	127
Additive Pour Point °F (ASTM D97)	<-50°F
Viscosity @ 77°F cP (Brookfield)	4.62
NOTE: The sulfur content of this fuel additive does not exceed 15 ppm.	

AVAILABLE PACKAGING

- 300 gal totes
- 55 gal
- 2.5 gal