



PRODUCT DATA SHEET

CGX-4®

HIGH PERF. PREMIUM LPG/PROPANE AUTO GAS ADDITIVE with CH25X® Technology (CGX4)

APPLICATIONS

CGX-4® with CH25X® Technology can be used to formulate a high-performance Premium LPG/propane fuel. CGX-4® is documented to improve the quality of LPG/ Propane used in all types of propane applications. Typical applications include forklifts, auto gas locations, LPG Engines and LPG converted engines.

BLENDING RECOMMENDATIONS

Product can be added to bulk propane storage during delivery of fuel. Storage tank should have a 20% heel of fuel and be free of excess water and/or sludge.

Treat Rate

1:2000

Maximum Dosage: Dosage for this product should not exceed 1 gallon per 1000 gallons of propane.

Additive performance depends on the specific fuel being treated and condition of storage tanks.

SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Material Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and sellers obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of Illinois.

TYPICAL SPECIFICATIONS

ColorBrown
Specific Gravity @ 68° F (ASTM D891) 0.822
Density, lbs./gal. (Calculated)6.85
Flash Point °F, TCC (ASTM D3278) >109
Additive Pour Point °F (ASTM D97).....N/A
Viscosity @ 68° F cP (Brookfield).....1.56



Warning: Cancer –
www.p65warnings.ca.gov

PACKAGING

Available in bulk, 300 gal. totes, 55 gal. and 2.5 gal. containers.